

VALEURS D'ISOLATION PHONIQUE

Sonodec ® 250, TRD250

Sonodec ® 250 (Test report Nr. AB323-2 Peutz bv - The Netherlands)							
D _n (mm)	L (m)	Atténuation dB - Mid-frequez, HZ					
		125	250	500	1000	2000	4000
80	1	16	25	34	38	30	20
	2	22	37	48	54	46	30
	3	30	43	41	43	55	43
100	1	11	25	31	36	23	15
	2	17	31	51	50	38	26
	3	20	44	51	52	51	33
125	1	11	19	23	27	25	19
	2	17	31	43	43	35	22
	3	21	40	45	48	47	27
160	1	15	26	22	27	18	13
	2	22	38	35	39	29	20
	3	33	43	39	43	39	27
200	1	6	13	15	18	11	10
	2	15	31	32	38	21	18
	3	16	36	40	42	28	24
250	1	9	11	12	10	7	11
	2	21	24	24	22	13	15
	3	29	33	31	30	19	24
315	1	8	8	8	7	6	8
	2	16	15	14	13	9	13
	3	23	23	21	19	12	17
450	1	8	8	6	6	5	7
	2	18	15	14	12	8	10
	3	24	21	20	18	11	15
500	1	7	8	7	7	6	7
	2	-	-	-	-	-	-
	3	-	-	-	-	-	-

Ces valeurs d'isolation sont seulement valables pour les tuyaux mentionnés ci-dessus